



MORBARK

MADE FOR **MORE** TO KEEP PACE WITH **YOU**



**EGER
BEEVER**

2230 BRUSH CHIPPER

Ideal for entry-level biomass production, lot and land clearing contractors, contractors and large tree services, this high-capacity, high-production chipper has more standard features than any other chipper in its class and is offered in a variety of configurations for incredible versatility.

The **Eger Beaver 2230** is available in a wide variety of configurations. Select the two-speed, steel track undercarriage with 4.24psi ground pressure and take the chipper to the material. Add the optional 5' (1.5 m) infeed deck for no-hassle feeding. The versatile, high-performance Forestry model, built heavier in critical wear areas, provides optimal performance for in-woods chipping. Or add a powerful Mor-Lift Model 150M hydraulic knuckleboom loader.

FEATURES AND BENEFITS

- The powerful TorqMax™ Plus dual feed wheel compression system generates more than 10,000 ft-lb (4,536 Nm) of material pulling force.
- The Variable Force™ Hydraulic Down Pressure System eliminates the use of springs and creates up to 10,000 lb (4,536 kg) of perpetual down pressure.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and aids in discharging light, leafy material.
- 29.125" (74 cm) wide x 37.375" (94.9 cm) diameter, six-knife staggered-pocket cutting system with patented removable knife holders increases chipping capacity.
- Bearing-style pivot assembly contours the radius of the drum, increases down pressure efficiency and reduces feed wheel dead space.



MORBARKDEALERS.COM



MORBARK

**EEGER
BEEVER**

2230 BRUSH CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 10/30/18

GENERAL	US	METRIC
Height	10'1.5"	3.09 m
Width	8'5.5"	2.58 m
Length	21'2"	6.45 m
Gross weight (approximate)	14,700 lb	6,668 kg
Suspension	(2) 10,000 lb Torflex	(2) 4,536 kg Torflex
Infeed opening (height x width)	39" x 65"	99.1 x 165.1 cm
Throat opening (height x width)	22" x 30"	55.9 x 76.2 cm
Drum (width x diameter)	29.1" x 37.4"	74 x 94.9 cm
Engine	CAT	
Horsepower	335 – 415 HP	249.8 – 309.5 kW
Fuel capacity	65 gallons	246 L
Hydraulic capacity	45 gallons	170.3 L
Frame	2" x 8" Tubular	5.1 x 20.3 cm Tubular
Tires	(4) 235/75Rx17.5	
Hitch	3" Pintle	7.6 cm Pintle

EQUIPMENT HIGHLIGHTS

- Dual horizontal feed wheels with TorqMax Plus™ top feed wheel compression system, hydraulic lift assist, Variable Force™ constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and sprocket driven bottom feed wheel
- 360° height-adjustable, hydraulic swivel discharge chute with chip deflectors
- Serrated teeth and knife bars on top and bottom feed wheels
- Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
- Discharge clean-out door on bottom
- Hydraulic front stabilizer

OPTIONS INCLUDE

- Variable Speed Flow Control
- Turnbuckle for Discharge Height Adjustment
- Winch Package: heavy-duty, 5,000 lb (2268 kg) pull capacity with rope and 10' (3 m) chafe guard
- Custom Paint and Logo Packages
- Wireless 15-function, 900Mhz Remote Control with tethered back-up system and electric over hydraulic actuator for control bar
- Dual Rear Hydraulic Stabilizers
- Axle Options Available
- Strobe Light

