

As part of the 300 Series, the gas-powered **385D Mini Skid Steer** offers the power that Boxer has become known for in a smaller package, allowing you to reduce overhead and increase jobsite productivity. Designed to handle a full complement of attachments, the 385D helps minimize hand labor. Because of its reduced size and ease of operation, the 385D is ideal for the rental industry. This compact machine provides the strength to perform a variety of tasks and the versatility to get into tight area.

FEATURES AND BENEFITS

- 24.8-HP (18.49 kW) Kubota D902 Diesel Engine
- 1,100 lb (493 kg) tip capacity
- 385lb (174.6 kg) operation capacity (35% tip load)
- 35" (889 mm) wide to fit through a standard gate
- Two-pump, 2,800 psi (193 bar) hydraulic operating system develops optimum hydraulic flow to run the machine's auxiliary and propulsion systems, providing enough power to handle full-size attachments
- Dedicated oil cooler to better manage hydraulic heat generation
- Stand-on platform for operator safety and comfort
- 2-button pressure relief block
- 2.5" (64 mm) bore-welded tilt cylinder and 3" (76 mm) bore-welded lift cylinder
- 0.25" (6 mm) thick laser-cut base sides and 0.75" (19 mm) thick boom arms
- · Well-balanced and stable, with excellent ground speed
- Universal compact utility loader mounting plate and quick-attach system to quickly and easily switch between any standard attachment





| SPECIFICATION | US | METRIC |
|-------------------------------------|-------------|-------------|
| Engine Type | Kubota | |
| Cooling System | Air-Cooled | |
| HP/kW | 24.8 HP | 18.49 kW |
| Fuel Type | Diesel | |
| Fuel Capacity | 4.5 Gallons | 17.1 Litres |
| Hydraulic Capacity | 16 Gallons | 60.6 Litres |
| System Flow (Total) | 11 GPM | 41.6 L/min |
| Hydraulic Flow (Aux) | 8.0 GPM | 30.3 L/min |
| Hydraulic Flow (Drive) | 3.0 GPM | 11.4 L/min |
| System Pressure | 2800 PSI | 19305.3 kPa |
| Engine Warranty | 3 years | |
| Product Warranty | 1 year | |
| Track Gauge | 27.5" | 699 mm |
| Track Width | 7" | 180 mm |
| Weight (No Attachment) | 1913 lb | 867.72 kg |
| Length (No Attachment) | 68" | 1727 mm |
| Length (w/Bucket) | 93" | 2362 mm |
| Width (Overall) | 35" | 889 mm |
| Height (Boom Lowered) | 48" | 1219.2 mm |
| Height (Boom Raised) | 92" | 2337 mm |
| Hinge Pin Height | 70" | 1778 mm |
| Dump Height | 54" | 1372 mm |
| Dump Angle | 34 Degrees | |
| Reach | 28" | 711 mm |
| Tip Capacity | 1,100 lb | 498.9 kg |
| Operating Capacity, 35% of tip load | 385 lb | 174.6 kg |
| Ground Clearance | 5" | 127 mm |
| Ground Speed | 3.4 MPH | 5.5 km/h |
| Ground Pressure | 3.8 PSI | 26.2 kPa |
| | | |

Updated 2/8/23

