

# Maverick 2

*Mid-Mount Boom Mower*



## Built for Strength

Built to resemble the strength & durability of a backhoe arm, the Maverick 2 has strength where needed.

## Mow Inches from the Tire

180° swing path allows the operator to mow within 6" of the tire.

## Maximum Reach of 30'

Four bar linkage allows the cutting head to be maneuvered at greater angles making it easier to cut in hard-to-reach areas.

Piston pump boom with a turret-style mount giving it a 180° front to back hydraulic swing.

## Boom Reach Options

24', 28' and 30'

\*with 60" Rotary Head

## Other Available Attachments

Battle Axe

Ditcher

Flail Axe®

HD Grass Flail

SD Rotary Head

SRD50 Mulcher

Buzz Bar®

Timber Cat

## Tractor Minimums

10,500lbs & 90PTO HP

90" wheelbase

18" ground clearance

CAB



**[Alamo-Industrial.com](http://Alamo-Industrial.com) | [sales@alamo-industrial.com](mailto:sales@alamo-industrial.com)**

©2022 Alamo Industrial or its affiliates. 2022 Alamo Group Texas All rights reserved. This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products. Warranty: One year limited parts and labor. Non-governmental users are subject to modified policy. Only genuine Alamo Industrial parts should be used for warranty replacement.

Sourcewell - Contract No. 070821-AGI  
Canoe Canada - Contract No. 070821-AGI  
GSA - Contract No. GS-30F-0008S  
Buy Board - Contract No. 611-20





**////ALAMO<sup>®</sup>**  
**INDUSTRIAL**

**Maverick 2**