

# XL FLAT DECK EXTENDABLE



- Available in 48-foot or 53-foot overall length
- Sliding tandem axles
- Stake pockets on 24" centers
- 5/16" x 2" rub rail with double pipe spools
- 6-inch structural side rails
- Plug and play rubber mounted LED lights
- 4 stake pockets across front channel for headboard






## PROVEN EXTENDABLE TECHNOLOGY


The XL FDE uses XL's patented Extend-a-trac to extend and retract the deck without hooking and unhooking air and electrical lines. The air operated lock pins have extension stops every 60 inches. Four 6-inch greasable rollers make extending and retracting the trailer smooth.

## **VERSATILE AXLE OPTIONS**

Haul a variety of loads with the XL 80 FDE; sliding tandem axles adjust using a simple lock pin to work best with each load's specific weight distribution. The FDE is available with four axle-spread options: 49-inch (with spring suspension only), 54-inch, 60-inch or 10-foot 1-inch. The 48-foot long rear deck features a 58-inch loaded deck height.

DESIGNED FOR YOU. BUILT TO LAST.





## **XL 70 CAPACITY**

capacity: 70,000 lb overall concentrated: 50,000 lb in 10'

#### XL 80 CAPACITY

capacity: 80,000 lb overall concentrated: 60,000 lb in 10'

#### **OVERALL LENGTH & WIDTH**

overall length: 48'-81' overall width: 102"

## **FRONT DECK**

10' long

49" 5th wheel height

2 speed landing gear with handle

curbside

24" king pin setting

82" swing clearance

4 stake pockets across front

channel for headboard

5/16" x 2" rub rail with double pipe spools

steel winch track on driverside

12 steel winches

11/8" Apitong decking - flush

1 pair flag holders

registration holder

#### **REAR DECK**

38' long

T-1 flange, 80K web

extend-a-trac

air operated lock pins with extension

stops on 60" centers

(4) 6"greasable rollers

58" loaded deck height sliding tandem

stake pockets on 24" centers

5/16" x 2" rub rail with double

pipe spools

6" structural side rails

1 pair flag holders

4" jr. i-beam cross members

on 12" centers

1 1/8" Apitong decking - flush stake pockets in tail channel for

wide load sign

dock bumpers

#### **REAR DECK OPTIONS**

spare tire carrier

1 3/8" Apitong decking - raised additional 2" side clearance lights

4" amber strobe tail light

(1) 4-way plug

48" head board (non-wrap around) side load sign

#### **SUSPENSION**

25.000 lb air ride

#### **SUSPENSION OPTIONS**

liquid filled air gauge spring suspension manual ride height control Air-weigh digital scape

## **AXLES**

(2) 25,000 lb nominal hub pilot, outboard drums 4S2M spring brakes on 2 axle limit straps 16 1/2" x 7" brakes 77 1/2" tracking

## **AXLE OPTIONS**

54" axle spacing

60" axle spacing

10' 1" axle spacing

49" axle spacing (spring suspension

only)

PSI tire inflation system

hubometer

cam covers and dust shields

#### **WHEELS & TIRES**

8.25 x 22.5 steel rims 11R / 22.5 tires

#### WHEEL & TIRE OPTIONS

aluminum mill wheels (inside) aluminum mill wheels (outside) aluminum polished wheels (outside) aluminum Durabright wheels (outside)

#### **LIGHTING**

12V sealed Grote harness rubber mounted LED lights 2 tail light package with aluminum cover

3 clearance lights per side

1 mid-turn light per side

7 pole electric socket

#### **PAINT**

black, IH red, CAT yellow or white air & electric done after paint

#### **PAINT OPTIONS**

non-standard paint colors non-standard metallic paint

#### **WARRANTY**

5 year structural 3 year paint

## **AVAILABLE MODELS**

XL 70 FDE

XL 80 FDE

other custom capacities also available, ask your sales representative for details