

XL POWER TAIL



FEATURES

- Foot hole and grab handle for access to upper deck
- 9-foot pop-up ramp from deck to neck
- 25,000 lb tail lifting capacity
- · Work light at rear of neck
- · Two function wireless remote
- Star traction or steel tread plate



LEOPT ** **Fork

UNIQUE HYDRAULIC TAIL DESIGN

The tail is comprised of two sections – an 8-foot 8-inch platform ramp and a 60-inch flip tail. Both hinge points stay clean thanks to lug style hinges. These hinges prevent debris from accumulating.

HANDLES HARD-TO-LOAD EQUIPMENT

With a load angle of 10 degrees, the hydraulic tail is equipped to easily handle hard-to-load equipment such as manlifts, rollers, forklifts and paving equipment. The tail features a lifting capacity of 25,000 pounds for loads centered on the main platform.

DESIGNED FOR YOU. BUILT TO LAST.

POWER TAIL SPE(

CAPACITY

capacity: 80,000 lb overall concentrated: 50,000 lb in 10'

OVERALL LENGTH & WIDTH

overall length: 48' or 53' overall width: 102"

GOOSENECK

9' long full-width 90° slope

16" king pin setting

86" swing clearance

49" 5th wheel height

steel tread plate decking

(2) d-rings per side

2 speed landing gear with handle on driver side

wet line hydraulics to run off truck hydraulic levers on driver side

planetary drive 18,000 lb hydraulic winch with 75' of 1/2" cable

WINCH WITH 75 OF I

& air kick out

2 function wireless remote

for winch

2 toolboxes with lids

9' long pop-up ramp, deck to neck integrated foot step and grab

handle, on both sides

GOOSENECK OPTIONS

13HP Honda power unit

no pop-up ramp

 $30,000 \, lb \, winch$

20,000 lb winch

12,000 lb winch

work-around pulley for winch cable

bolt-on winch guard

8 function wireless remote

10 function wireless remote

registration holder

MAIN DECK

T-1 flange, 80k web 48' OAL: 30' 4" long 53' OAL: 35' 4" long 36" loaded deck height

13/8" Apitong decking - raised

1/4" tread plate covered wheels

18" fabricated i-beams

 $10\ensuremath{\text{"}}$ & 8 $\ensuremath{\text{"}}$ jr. i-beam cross members on

alternating 12" centers

5 d-rings per side

stake pockets and chain slots

on alternating 24" centers, sides

chain slots down on 48" centers, center deck

MAIN DECK OPTIONS

double drop design additional d-rings

TAIL SECTION

13' 8" hydraulic tail:

8'8" platform

60" fold under flip tail

automatic flip tail lock

traction aids

star traction plate decking

TAIL SECTION OPTIONS

steel tread plate decking in lieu of star plate

WHEELS & TIRES

6.75 x 17.5 steel rims 245 / 70R / 17.5 tires

WHEEL & TIRE OPTIONS

255 tires changes rear

deck height to 39"

aluminum mill wheels

*aluminum polished wheels (outside)

customer specified tires

customer specified mud flaps

Michelin tires

PSI tire inflation system

SUSPENSION

25,000 lb air ride

SUSPENSION OPTIONS

*liquid filled air gauge *Air-weigh digital scale

AXLES

(2) 25,000 lb nominal 49" axle spacing hub pilot, outboard drums 4S2M ABS spring brakes on 2 axles 12 1/4" x 7 1/2" brakes auto slack adjusters air dump on both axles

AXLE OPTIONS

hubometer

TP axles (same inner & outer bearings)

dust shields

cat eye systems

disc brakes

LIGHTING

12V sealed Grote harness rubber mounted led lights

3 tail light package

1 mid-turn signal per side

2 clearance light per side

7 pole electrical socket

LIGHTING OPTIONS

*amber strobe as 3rd tail light additional clearance lights

PAINT

black, IH red, CAT yellow or white air & electric done after paint

PAINT OPTIONS

custom paint colors metallic paint colors

WARRANTY

5 year structural 3 year paint