

DENIS  **CIMAF**®

DAF

**SKID STEER-MOUNTED
MULCHING ATTACHMENT
SPECIFICATIONS**



DENIS CIMAF®

DAF SKID STEER-MOUNTED MULCHING ATTACHMENT SPECIFICATIONS

SPECIFICATION	DAF-250Ex	DAF-225Ex	DAF-225E	DAF-180E	DAF-180D	DAF-150D
Approximate Min. Carrier Power	250 HP (190 kW)	200 HP (150 kW)	175 HP (130 kW)	125 HP (95 kW)	85 HP (65 kW)	75 HP (60 kW)
Cutting Width	99" (251 cm)	85" (216 cm)	88" (223cm)	74" (188 cm)	74" (188 cm)	59" (150 cm)
Cutting Distance from Ground Level	.4" (1 cm)	.4" (1 cm)	.4" (1 cm)	.8" (2 cm)	.8" (2 cm)	.8" (2 cm)
Number of Blades on Rotor	35	31	31	27	27	21
Optimal Target Material Diameter	24" (61 cm)	24" (61 cm)	15" (38 cm)	10" (25 cm)	8" (20 cm)	6" (15 cm)
Exterior Width	103" (261 cm)	102" (259 cm)	100" (254 cm)	88" (223 cm)	87" (221 cm)	72" (183 cm)
Exterior Height (with Pushbar)	61" (155 cm)	58" (147 cm)	55" (140 cm)	55" (139 cm)	58" (147 cm)	59" (150 cm)
Exterior Height (without Pushbar)	38" (97 cm)	38" (97 cm)	38" (97 cm)	37" (94 cm)	44" (112 cm)	26" (66 cm)
Exterior Depth (with Pushbar)	50" (127 cm)	51" (130 cm)	55" (140 cm)	45" (114 cm)	51" (130 cm)	48" (122 cm)
Exterior Depth (without Pushbar)	33" (84 cm)	33" (84 cm)	33" (84 cm)	27" (69 cm)	31" (79 cm)	29" (74 cm)
Rotor Diameter	20" (51 cm)	20" (51 cm)	20" (51 cm)	20" (51 cm)	18" (46 cm)	18" (46 cm)
Weight, typical (estimated)	5400 lb (2449 kg)	5200 lb (2359 kg)	4700 lb (2132 kg)	3300 lb (1497 kg)	3200 lb (1452 kg)	2300 lb (1043 kg)
HYDRAULIC SYSTEM	DAF-250Ex	DAF-225Ex	DAF-225E	DAF-180E	DAF-180D	DAF-150D
Variable Displacement Axial Piston Motor	2	2	1	1	1	1
Max. Cyl.	115	115	170	170	115	85
Max. Motor Torque (T max at Vg max), lbs-ft	502	502	907	502	502	450
Nm	681	681	1230	681	681	610
Required Continuous Flow*	80 gal/min (303 L/min)	75 gal/min (284 L/min)	60 gal/min (227 L/min)	50 gal/min (189 L/min)	35 gal/min (132 L/min)	23 gal/min (87 L/min)
Operating Pressure*	6000 psi (414 bar)	6000 psi (414 bar)	6000 psi (414 bar)	6000 psi (414 bar)	5000 psi (345bar)	5000 psi (345bar)
Rotating Speed	2250 r/min	2250 r/min	2350 r/min	2400 r/min	2550 r/min	2600 r/min
Pressure Line I.D.	1.25" (#20)	1.25" (#20)	1" (#16)	1" (#16)	1" (#16)	.75" (#12)
Return Line I.D.	1.25" (#20)	1.25" (#20)	1" (#16)	1" (#16)	1" (#16)	.75" (#12)
Drain Line	1" (#16)	1" (#16)	.75" (#12)	.675" (#10)	.675" (#10)	.625" (#10)
FEATURES	DAF-250Ex	DAF-225Ex	DAF-225E	DAF-180E	DAF-180D	DAF-150D
Sharpenable Bolt-on Forged Blades	Standard	Standard	Standard	Standard	Standard	Standard
Hydraulic Pushbar	√	√	√	√	√	√
Bolt-in Wear Liner	√	√	√	√	√	√

These are minimum requirements; call your Denis Cimaf Sales Representative for guidance in selecting the best match for your equipment.

(current as of 8/16/22)